



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

1 Identification of the substance/mixture and of the company/undertaking

- Product identifier
- Trade name: **KRISTAL HS Hardener LV STD**
- Article number: 8040
- Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the preparation Hardening agent/ Curing agent
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Kristal Coatings B.V.
Platinawerf 22B
6641 TL Beuningen - Holland
Tel: 0031 24 67 526 36
Fax: 0031 24 67 533 60
- Information department: Product safety department: info@kristalcoatings.nl
- Emergency telephone number: 0031 24 67 526 36

2 Hazards identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.

- Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Harmful

Harmful by inhalation.



Irritant

Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.



Highly flammable

Highly flammable.

Harmful to aquatic organisms.

- Information concerning particular hazards for human and environment:
The product has to be labelled due to the calculation procedure of international guidelines.
- Classification system:
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- Label elements
- GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS07

(Contd. on page 2)

USA



Safety Data Sheet


acc. to ISO/DIS 11014


Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 1)

- Signal word Danger
 - Hazard-determining components of labelling:
Hexane, 1,6-diisocyanato-, homopolymer
 - Hazard statements
Highly flammable liquid and vapour.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
 - Precautionary statements
Take precautionary measures against static discharge.
Do not breathe mist/vapours/spray.
Wear protective gloves and eye/face protection.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Dispose of contents/container in accordance with local/regional/national/international regulations.
 - Classification system:
 - NFPA ratings (scale 0 - 4)
- 

Health = 2
Fire = 3
Reactivity = 0
- HMIS-ratings (scale 0 - 4)
- 

HEALTH 2 Health = 2
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0
- Other hazards
 - Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 28182-81-2 EC number: Polymer Reg.nr.: 01-2119485796-17	Hexane, 1,6-diisocyanato-, homopolymer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 98-56-6 EINECS: 202-681-1 Reg.nr.: 1735902	4-chloro-alpha,alpha,alpha-trifluorotoluene ⚠ Flam. Liq. 3, H226; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49 05-2114366599-29	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 01-2119486136-34 01-2119555267-33	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; STOT SE 3, H335-H336; H227	0.5-2.5%

(Contd. on page 3)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 2)

CAS: 123-86-4

n-butyl acetate

0.5-2.5%

EINECS: 204-658-1

Flam. Liq. 3, H226; STOT SE 3, H336

Reg.nr.: 01-2119485493-29

4 First aid measures

- Description of first aid measures
- General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Firefighting measures

- Extinguishing media
- Suitable extinguishing agents: CO₂ or powder. Fight larger fights with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Carbon monoxide (CO)
- Advice for firefighters
- Protective equipment:
Mouth respiratory protective device.
Wear self-contained respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.
Examination of lung function should be carried out on a regular basis on persons spraying this preparation.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 3)

- Conditions for safe storage, including any incompatibilities
- Storage:
 - Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Store away from oxidizing agents.
 - Further information about storage conditions:
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.
 - Storage class: 3
 - Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppmREL 590 mg/m³, 250 ppmTLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppmLong-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm

BEI

1330-20-7 xylene

PEL 435 mg/m³, 100 ppmREL Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLV Short-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppm

BEI

123-86-4 n-butyl acetate

PEL 710 mg/m³, 150 ppmREL Short-term value: 950 mg/m³, 200 ppmLong-term value: 710 mg/m³, 150 ppmTLV Short-term value: 950 mg/m³, 200 ppmLong-term value: 713 mg/m³, 150 ppm

- Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

- Additional information:

The lists that were valid during the creation were used as basis.

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is used.

Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the eyes and skin.

(Contd. on page 5)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Color: Clear

· Odor: Characteristic

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 56 °C (133 °F)

· Flash point: -8 °C (18 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 465 °C (869 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 2.6 Vol %

Upper: 13.0 Vol %

· Vapor pressure at 20 °C (68 °F): 233 hPa (175 mm Hg)

· Density at 20 °C (68 °F): 1.12 g/cm³ (9.346 lbs/gal)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

(Contd. on page 6)

USA



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 5)

- Solubility in / Miscibility with Water: Insoluble.
- Partition coefficient (n-octanol/water): Not determined.
- Viscosity:
 - Dynamic: Not determined.
 - Kinematic at 20 °C (68 °F): 12 s (DIN 53211/4)
- Solvent content:
 - Organic solvents: 60.8 %
 - VOC content: 12.3 %
 - 138.0 g/l / 1.15 lb/gl
- Solids content: 39.2 %
- Other information: No further relevant information available.

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions
 - Reacts with alcohols.
 - Reacts with amines.
 - Reacts with water.
- Conditions to avoid: No further relevant information available.
- Incompatible materials: Oxidizing agents.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)
 Dermal LD50 7800 mg/kg (rabbit)
 Inhalative LC50/4h > 20 mg/l (rat)

1330-20-7 xylene

Oral LD50 2000-5000 mg/kg (l)
 Inhalative LC50 10-20 mg/l (l)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)
 Dermal LD50 >3400 mg/kg (rab)
 Inhalative LC50/4h >10.2 mg/l (rat)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Harmful
 - Irritant
- Carcinogenic categories
- IARC (International Agency for Research on Cancer)
 - 1330-20-7 xylene: 3

(Contd. on page 7)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

67-64-1 acetone

EC50 8800 mg/l (daphnia magna)

EC50/96h 8300 mg/l (Iepomis macrochirus)

IC50 >100 mg/l (algae)

>100 mg/l (fish)

1330-20-7 xylene

EC50/48h 7.4 mg/l (daphnia magna)

IC50 1-10 mg/l (TISBE Marine copepod)

1-10 mg/l (algae)

> 100 mg/l (bacteria)

1-10 mg/l (fish)

NOAEL 0.1-1 mg/l (TISBE Marine copepod)

1-10 mg/l (fish)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN1263

· UN proper shipping name

· DOT, IMDG, IATA

PAINT

· ADR

1263 PAINT

(Contd. on page 8)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.
 · Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids
 · Label 3
 · Packing group
 · DOT, ADR, IMDG, IATA II
 · Environmental hazards:
 · Marine pollutant: No
 · Special precautions for user Warning: Flammable liquids
 · Danger code (Kemler): 33
 · EMS Number: F-E,S-E
 · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
 · UN "Model Regulation": UN1263, PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

822-06-0 hexamethylene-di-isocyanate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1 acetone: I

1330-20-7 xylene: I

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone: A4

1330-20-7 xylene: A4

(Contd. on page 9)

— USA —



Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 12/06/2012

Reviewed on 12/06/2012

Trade name: **KRISTAL HS Hardener LV STD**

(Contd. of page 8)

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02

GHS07

- Signal word Danger

- Hazard-determining components of labelling:

Hexane, 1,6-diisocyanato-, homopolymer

- Hazard statements

Highly flammable liquid and vapour.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

- Precautionary statements

Take precautionary measures against static discharge.

Do not breathe mist/vapours/spray.

Wear protective gloves and eye/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- National regulations:

- Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Contact: Dhr. B. Peters

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent