



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **KRISTAL 2K Drying Booster**
- Article number: 3121
- 1.2 Relevant identified uses of the substance or mixture and uses advised against  
No further relevant information available.
- Application of the substance / the mixture Accelerator
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
Kristal Coatings B.V.  
Platinawerf 22B  
6641 TL Beuningen - Holland  
Tel: 0031 24 67 526 36  
Fax: 0031 24 67 533 60
- Further information obtainable from: Product safety department: info@kristalcoatings.nl
- 1.4 Emergency telephone number:  
National Poisoning Information Centre - Bilthoven - The Netherlands  
T +31 (0)30 274 88 88  
Restricted to physicians for information on ingredients.

### SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3	H226	Flammable liquid and vapour.
--------------	------	------------------------------



GHS08 health hazard

STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
-------------------	------	--

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labelling:  
xylene  
n-butyl acetate
- Hazard statements  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

(Contd. on page 2)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 1)

- H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.  
 H412 Harmful to aquatic life with long lasting effects.

### · Precautionary statements

- P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P260 Do not breathe mist/vapours/spray.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### · Additional information:

- EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.  
 Restricted to professional users.

### · 2.3 Other hazards

### · Results of PBT and vPvB assessment

- PBT: Not applicable.  
 · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 123-86-4	n-butyl acetate	25-50%
EINECS: 204-658-1	⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 1330-20-7	xylene	25-50%
EINECS: 215-535-7	⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119488216-32		
01-2119486136-34		
01-2119555267-33		
CAS: 100-41-4	ethylbenzene	2,5-10%
EINECS: 202-849-4	⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Aquatic Chronic 3, H412	
CAS: 77-58-7	dibutyltin dilaurate	≤ 0,5%
EINECS: 201-039-8	⚠ Muta. 2, H341; Repr. 1A, H360FD; STOT SE 1, H370; STOT RE 1, H372; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	
Reg.nr.: 01-2119496068-27		

- Additional information: For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · General information:

- Immediately remove any clothing soiled by the product.  
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
 In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

- Immediately wash with water and soap and rinse thoroughly.  
 If skin irritation continues, consult a doctor.

#### · After eye contact:

- Rinse opened eye for several minutes under running water. Then consult a doctor.  
 Remove contactlenses.

#### · After swallowing:

- Do not induce vomiting; call for medical help immediately.  
 Rinse mouth.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 2)

- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO<sub>2</sub> or powder. Fight larger fights with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- 7.1 Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:  
· Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 1330-20-7 xylene

IOELV Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

#### 100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Skin

- DNELs

#### 123-86-4 n-butyl acetate

Inhalative Acute - short-term exposure - local effects 960 mg/m<sup>3</sup> (worker)  
Acute - short-term exposure - systemic effects 960 mg/m<sup>3</sup> (worker)

(Contd. on page 4)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 3)

Long-term exposure - local effects 480 mg/m<sup>3</sup> (worker)  
 Long-term exposure - systemic effects 480 mg/m<sup>3</sup> (worker)

**1330-20-7 xylene**

Dermal Long-term exposure - systemic effects 180 mg/kg bw/day (worker)  
 Inhalative Acute - short-term exposure - local effects 289 mg/m<sup>3</sup> (worker)  
 Acute - short-term exposure - systemic effects 289 mg/m<sup>3</sup> (worker)  
 Long-term exposure - systemic effects 77 mg/m<sup>3</sup> (worker)

**100-41-4 ethylbenzene**

Dermal Acute - short-term exposure - local effects 293 mg/kg bw/day (worker)  
 Long-term exposure - systemic effects 180 mg/kg bw/day (worker)  
 Inhalative Long-term exposure - systemic effects 77 mg/m<sup>3</sup> (worker)

**77-58-7 dibutyltin dilaurate**

Dermal Acute - short-term exposure - systemic effects 1 mg/kg bw/day (worker)  
 Long-term exposure - systemic effects 0,2 mg/kg bw/day (wki)  
 Inhalative Acute - short-term exposure - systemic effects 0,07 mg/m<sup>3</sup> (wki)  
 Long-term exposure - systemic effects 0,01 mg/m<sup>3</sup> (wki)

**PNECs****123-86-4 n-butyl acetate**

PNEC 35,6 mg/l (STP)  
 0,18 mg/l (aqua, freshwater)  
 0,36 mg/l (aqua, intermittent releases)  
 0,018 mg/l (aqua, marine water)  
 0,0981 mg/l (sediment marine water)  
 0,981 mg/kg (sediment freshwater)

**1330-20-7 xylene**

PNEC 6,58 mg/l (STP)  
 0,237 mg/l (aqua, freshwater)  
 0,327 mg/l (aqua, intermittent releases)  
 0,327 mg/l (aqua, marine water)  
 12,46 mg/kg (sediment marine water)

**100-41-4 ethylbenzene**

PNEC 9,6 mg/l (STP)  
 0,1 mg/l (aqua, freshwater)  
 0,1 mg/l (aqua, intermittent releases)  
 0,01 mg/l (aqua, marine water)  
 13,7 mg/kg (sediment freshwater)  
 2,68 mg/kg (soil)

**77-58-7 dibutyltin dilaurate**

PNEC 100 mg/l (STP)  
 0,000463 mg/l (aqua, freshwater)  
 0,00463 mg/l (aqua, intermittent releases)  
 0,0000463 mg/l (aqua, marine water)  
 0,005 mg/kg (sediment marine water)  
 0,05 mg/kg (sediment freshwater)

Additional information: The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Do not inhale gases / fumes / aerosols.  
 Avoid contact with the eyes and skin.

(Contd. on page 5)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 4)

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Filter A.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber gloves (Viton)

- **Penetration time of glove material**

Thickness of the gloves  $\geq 0.7$  mm (xylenes)

Value for the permeation  $\geq 480$  min (xylenes)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Solvent resistant protective clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Colour: Clear

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 124 °C

- **Flash point:** 24 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: 1,1 Vol %

Upper: 7,5 Vol %

- **Vapour pressure at 20 °C:** 10,7 hPa

- **Density at 20 °C:** 0,88 g/cm<sup>3</sup>

- **Relative density** Not determined.

- **Vapour density** Not determined.

(Contd. on page 6)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 5)

- Evaporation rate Not determined.
- Solubility in / Miscibility with water: Slightly soluble.
- Partition coefficient (n-octanol/water): Not determined.
- Viscosity:
  - Dynamic at 20 °C: 1 mPas
  - Kinematic: Not determined.
- Solvent content:
  - Organic solvents: 99,7 %
  - VOC (EC) 99,74 %
- 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid High temperatures.
- 10.5 Incompatible materials: Oxidizing agents.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

#### 123-86-4 n-butyl acetate

Oral LD50 10760 mg/kg (rat) (OECD 423)  
 Dermal LD50 >14112 mg/kg (rabbit) (OECD 402)  
 Inhalative LC50/4h 23,4 mg/l (rat) (OECD 403 in vivo, aerosol)

#### 1330-20-7 xylene

Oral LD50 3523 mg/kg (rat)  
 Dermal LD50 12126 mg/kg bw (rabbit)  
 Inhalative LC50/4h 27124 mg/m<sup>3</sup> (rat)

#### 100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)  
 Dermal LD50 17800 mg/kg (rabbit)

#### 77-58-7 dibutyltin dilaurate

Oral LD50 2071 mg/kg (rat) (OECD 401)  
 Dermal LD50 >2000 mg/kg (rabbit) (OECD 402)

- Primary irritant effect:
- Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eye damage/irritation No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.

#### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful  
 Irritant

— EU —  
 (Contd. on page 7)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 6)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### **123-86-4 n-butyl acetate**

EC50/48h 44 mg/l (daphnia magna)

EC50/72h 647,7 mg/l (desmodesmus supspicatus)

IC50 356 mg/l (tetrahymena pyriformis) (40 h)

LC50/96h 18 mg/l (pimphales promelas) (OECD 203)

NOAEL/72h 200 mg/l (desmodesmus supspicatus)

##### **1330-20-7 xylene**

EC50/48h 7,4 mg/l (daphnia magna)

IC50 1-10 mg/l (TISBE Marine copepod)

1-10 mg/l (algae)

&gt; 100 mg/l (bacteria)

1-10 mg/l (fish)

NOAEL 0,1-1 mg/l (TISBE Marine copepod)

1-10 mg/l (fish)

##### **100-41-4 ethylbenzene**

EC50/24h &gt;100 mg/l (daphnia magna)

##### **77-58-7 dibutyltin dilaurate**

EC50/3h 1000 mg/l (bacteria) (OECD 209)

EC50/48h &lt; 1 mg/l (daphnia) (OECD 202)

EC50/72h &gt; 1 mg/l (algae) (OECD 201)

LC50/96h &gt; 3,1 mg/l (fish) (OECD 203)

#### · 12.2 Persistence and degradability No further relevant information available.

##### · Degree of elimination:

##### **123-86-4 n-butyl acetate**

OECD 301D 83 % (l) (28 d)

#### · 12.3 Bioaccumulative potential No further relevant information available.

#### · 12.4 Mobility in soil No further relevant information available.

##### · Ecotoxicological effects:

· Remark: Harmful to fish

##### · Additional ecological information:

##### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### · 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

#### · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### · European waste catalogue

07 01 04\* other organic solvents, washing liquids and mother liquors

##### · Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

### SECTION 14: Transport information

#### · 14.1 UN-Number

· ADR,ADN, IMDG, IATA

UN1263

(Contd. on page 8)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

Trade name: **KRISTAL 2K Drying Booster**

(Contd. of page 7)

- 14.2 UN proper shipping name
- ADR/ADN
- IMDG, IATA
- 14.3 Transport hazard class(es)
- ADR,ADN, IMDG, IATA

1263 PAINT RELATED MATERIAL

PAINT RELATED MATERIAL



- Class
- Label
- 14.4 Packing group
- ADR,ADN, IMDG, IATA
- 14.5 Environmental hazards:
- Marine pollutant:
- 14.6 Special precautions for user
- Danger code (Kemler):
- EMS Number:
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

3 Flammable liquids.

3

III

No

Warning: Flammable liquids.

30

F-E,S-E

Not applicable.

· Transport/Additional information:

- ADR/ADN
- Limited quantities (LQ)
- Excepted quantities (EQ)
- Transport category
- Tunnel restriction code

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

3

D/E

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN1263, PAINT RELATED MATERIAL, 3, III

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- National regulations:
- Other regulations, limitations and prohibitive regulations  
The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.

(Contd. on page 9)





# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.06.2015

Version number 5

Revision: 16.06.2015

---

**Trade name: KRISTAL 2K Drying Booster**


---

(Contd. of page 8)

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Contact:** Dhr. B. Peters

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Repr. 1A: Reproductive toxicity, Hazard Category 1A

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

— EU —