



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

1 Identification

- Product identifier
- Trade name: **KRISTAL TimeClear LV**
- Article number: 9400
- Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
- Application of the substance / the mixture Lacquer
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
Kristal Coatings B.V.
Platinawerf 22B
6641 TL Beuningen - Holland
Tel: 0031 24 67 526 36
Fax: 0031 24 67 533 60
- Information department: Product safety department: info@kristalcoatings.nl
- Emergency telephone number:
National Poisoning Information Centre - Bilthoven - The Netherlands
T +31 (0)30 274 88 88
Restricted to physicians for information on ingredients.

2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



GHS02



GHS07



GHS08

- Signal word Danger
- Hazard-determining components of labeling:
acetone
xylene
n-butyl acetate
Solvent naphtha (petroleum), light arom.
- Hazard statements
Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 1)

Suspected of causing cancer.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Do not breathe mist/vapours/spray.
 Wear protective gloves / eye protection.
 If swallowed: Immediately call a poison center/doctor.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization:** Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-64-1	acetone	10-25%
EINECS: 200-662-2		
Reg.nr.: 01-2119471330-49		
05-2114366599-29		
CAS: 123-86-4	n-butyl acetate	10-25%
EINECS: 204-658-1		
Reg.nr.: 01-2119485493-29		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
EINECS: 265-199-0		
Reg.nr.: 01-2119455851-35		
CAS: 110-43-0	heptan-2-one	0.5-2.5%
EINECS: 203-767-1		
CAS: 1330-20-7	xylene	0.5-2.5%
EINECS: 215-535-7		
Reg.nr.: 01-2119488216-32		
01-2119486136-34		
01-2119555267-33		
ELINCS: 400-830-7	Derivative of Benzotriazol	0.5-2.5%
Reg.nr.: 01-0000015075-76		
Reg.nr.: 01-2119491304-40	Reaction mass of pentamethylpiperidyl sebacat	0.5-2.5%
CAS: 100-41-4	ethylbenzene	≤ 0.5%
EINECS: 202-849-4		

— US —
 (Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 2)

4 First-aid measures

- Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Remove contactlenses.
- After swallowing:
Seek immediate medical advice.
Do not induce vomiting; immediately call for medical help.
Rinse out mouth and then drink plenty of water.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: CO₂ or powder. Fight larger fights with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Carbon monoxide (CO)
- Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about protection against explosions and fires:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
Store in a cool location.
Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Storage class: 3
- Specific end use(s) No further relevant information available.



Printing date 05/26/2015

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 3)

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm
 REL Long-term value: 590 mg/m³, 250 ppm
 TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
 Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm
 BEI

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm
 REL Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 710 mg/m³, 150 ppm
 TLV Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 713 mg/m³, 150 ppm

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm
 REL Long-term value: 465 mg/m³, 100 ppm
 TLV Long-term value: 233 mg/m³, 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

- Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes.
 Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
 Filter AX

- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 4)

Butyl rubber, BR

- Penetration time of glove material

Thickness of the gloves ≥ 0.625 mm (acetone)Value for the permeation: Level ≥ 480 min (acetone)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Solvent resistant protective clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties

- General Information

- Appearance:

Form:

Fluid

Color:

Clear

- Odor:

Characteristic

- Odour threshold:

Not determined.

- pH-value:

Not determined.

- Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

56 °C (133 °F)

- Flash point:

-10 °C (14 °F)

- Flammability (solid, gaseous):

Not applicable.

- Ignition temperature:

370 °C (698 °F)

- Decomposition temperature:

Not determined.

- Auto igniting:

Product is not selfigniting.

- Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- Explosion limits:

Lower:

1.2 Vol %

Upper:

13.0 Vol %

- Vapor pressure at 20 °C (68 °F):

233 hPa (175 mm Hg)

- Density at 20 °C (68 °F):

0.95 g/cm³ (7.928 lbs/gal)

- Relative density

Not determined.

- Vapour density

Not determined.

- Evaporation rate

Not determined.

- Solubility in / Miscibility with

Water:

Slightly soluble.

- Partition coefficient (n-octanol/water): Not determined.

- Viscosity:

Dynamic:

Not determined.

Kinematic at 20 °C (68 °F):

15 s (DIN 53211/4)

- Solvent content:

Organic solvents:

54.5 %

VOC content:

54.5 %

490.0 g/l / 4.09 lb/gal

(Contd. on page 6)

— US —



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 5)

· Other information No further relevant information available.

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Reacts with strong oxidizing agents.
- Conditions to avoid High temperatures.
- Incompatible materials: Oxidizing agents.
- Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

67-64-1 acetone

Oral LD50 >2000 mg/kg (rat)
 Dermal LD50 >2000 mg/kg (rabbit)
 Inhalative LC50/4h > 20 mg/l (rat)

123-86-4 n-butyl acetate

Oral LD50 10760 mg/kg (rat) (OECD 423)
 Dermal LD50 >14112 mg/kg (rabbit) (OECD 402)
 Inhalative LC50/4h 23.4 mg/l (rat) (OECD 403 in vivo, aerosol)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)
 Dermal LD50 >3400 mg/kg (rab)
 Inhalative LC50/4h >10.2 mg/l (rat)

110-43-0 heptan-2-one

Oral LD50 1670 mg/kg (rat)
 Dermal LD50 12600 mg/kg (rabbit)

1330-20-7 xylene

Oral LD50 3523 mg/kg (rat)
 Dermal LD50 12126 mg/kg bw (rabbit)
 Inhalative LC50/4h 27124 mg/m³ (rat)

Derivative of Benzotriazol

Oral LD50 >5000 mg/kg (rat) (OESO 401)
 Dermal LD50 >2000 ml/kg (rat) (OESO 402)
 Inhalative LC50/4h >5.8 mg/l (rat) (OESO 403)

100-41-4 ethylbenzene

Oral LD50 3500 mg/kg (rat)
 Dermal LD50 17800 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
 The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

- Carcinogenic categories
- IARC (International Agency for Research on Cancer)

1330-20-7 xylene: 3

100-41-4 ethylbenzene: 2B

(Contd. on page 7)

— US —



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

67-64-1 acetone

EC50	8800 mg/l (daphnia magna)
EC50/96h	8300 mg/l (lepomis macrochirus)
IC50	>100 mg/l (algae)
	>100 mg/l (fish)

123-86-4 n-butyl acetate

EC50/48h	44 mg/l (daphnia magna)
EC50/72h	647.7 mg/l (desmodesmus supspicatus)
IC50	356 mg/l (tetrahymena pyriformis) (40 h)
LC50/96h	18 mg/l (pimphales promelas) (OECD 203)
NOAEL/72h	200 mg/l (desmodesmus supspicatus)

1330-20-7 xylene

EC50/48h	7.4 mg/l (daphnia magna)
IC50	1-10 mg/l (TISBE Marine copepod)
	1-10 mg/l (algae)
	> 100 mg/l (bacteria)
	1-10 mg/l (fish)
NOAEL	0.1-1 mg/l (TISBE Marine copepod)
	1-10 mg/l (fish)

Derivative of Benzotriazol

EC10/72h (static)	10 mg/l (pseudokirchneriella subcapitata) (OESO 201)
EC50/3h (static)	>1000 mg/l (ac) (OESO 209)
EC50/48h (static)	4.0 mg/l (daphnia magna) (OESO 202)
EC50/72h (static)	>9 mg/l (algae) (OESO 201)
LC0/14d	>1000 mg/kg (Eisenia foetida) (OESO 207)
LC50/96h (static)	(oncorhynchus mykiss)
NOEC/21d (dynamic)	0.78 mg/l (daphnia magna) (OESO 202)
NOEC/56d	100 mg/kg (Eisenia foetida) (OESO 222)

Reaction mass of pentamethylpiperidyl sebacat

EC50/24h	20 mg/l (daphnia magna) (OESO 202)
EC50/3h	>100 mg/l (ac) (OESO 209)
EC50/72h (static)	1.68 mg/l (desmodesmus supspicatus) (OESO 201)
LC50/96h	0.97 mg/l (lepomis macrochirus) (OESO 203)
	0.9 mg/l (Brachydanio rerio) (OESO 203)
	7.9 mg/l (oncorhynchus mykiss) (OESO 203)
NOEC/21d (dynamic)	1 mg/l (daphnia magna) (OESO 211)

100-41-4 ethylbenzene

EC50/24h >100 mg/l (daphnia magna)

· Persistence and degradability No further relevant information available.

· Degree of elimination:

123-86-4 n-butyl acetate

OECD 301D 83 % (l) (28 d)

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

(Contd. on page 8)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 7)

- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Harmful to aquatic organisms
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number
- DOT, ADR,ADN, IMDG, IATA UN1263
- UN proper shipping name
- DOT Paint
- ADR/ADN 1263 Paint
- IMDG, IATA PAINT
- Transport hazard class(es)
- DOT



- Class 3 Flammable liquids
- Label 3

 · ADR,ADN, IMDG, IATA


- Class 3 Flammable liquids
- Label 3
- Packing group
- DOT, ADR,ADN, IMDG, IATA II
- Environmental hazards:
- Marine pollutant: No
- Special precautions for user Warning: Flammable liquids
- Danger code (Kemler): 33
- EMS Number: F-E,S-E
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 9)

— US —



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 8)

· Transport/Additional information:

· ADR/ADN

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN1263, Paint, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

67-64-1 acetone

123-86-4 n-butyl acetate

64742-95-6 Solvent naphtha (petroleum), light arom.

110-43-0 heptan-2-one

1330-20-7 xylene

112-07-2 2-butoxyethyl acetate

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

82919-37-7 methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

122-99-6 2-Phenoxyethanol

78-83-1 butanol

77-58-7 dibutyltin dilaurate

100-41-4 ethylbenzene

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1 acetone: I

1330-20-7 xylene: I

100-41-4 ethylbenzene: D

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: **KRISTAL TimeClear LV**

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)

67-64-1 acetone: A4

1330-20-7 xylene: A4

112-07-2 2-butoxyethyl acetate: A3

77-58-7 dibutyltin dilaurate: A4

100-41-4 ethylbenzene: A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

acetone

xylene

n-butyl acetate

Solvent naphtha (petroleum), light arom.

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Do not breathe mist/vapours/spray.

Wear protective gloves / eye protection.

If swallowed: Immediately call a poison center/doctor.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Other regulations, limitations and prohibitive regulations

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: Dhr. B. Peters

· Date of preparation / last revision 05/26/2015 / 1

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/26/2015

Reviewed on 05/26/2015

Trade name: KRISTAL TimeClear LV

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· * Data compared to the previous version altered.

— US —